

ASEPT.2X - MOBILE UV SURFACE PURIFICATION SYSTEM

Ship. Dim. /weight (bulk)	
Dim.	64.8" x 28" (1645 mm x 712 mm)
Weight	100 lbs (45.5 Kg)
Electrical	
Power	820W
Voltage	120/240 VAC, 60/50 Hz
Startup	START/STOP buttons, ON/OFF rocker switch
Circuit breaker	15 Amp
Construction	
Materials	Structural casing made of grade 316 stainless and anodized aluminum
Mobility	4x Medical grade casters, self lock, multidirectional
Number of ballasts	8
Connectivity	WI-FI (3 antennas), Web server accessible through smart devices or laptop
Accessories supplied	Tablette Android 7" (Or et Platine), Cône d'avertissement/coupleur, Panneaux de porte(2)
Safety	4x Motion detectors (PIR sensors), covering 360°
Lamps	
Type	Quartz Tube 3/4 " (19mm) T6- 4 pins
Number of lamps	8
Lamp type	Straight lamp, Teflon coated
Lamp length	40" (1016 mm)
UVC dosage	Sized according to room parameters. Consult a Sanuvox specialist.
Warranty	
Ballasts	5 years
Lamps	1 year
Electronic	1 year
Replacement parts	
Ballast(s) (8)	BST120/277SHS-F
UVC Lamp(s) (8)	LMPHGS400TF
PIR sensor (4)	ELC-DET-PIR-34

